

Mobil Delvac™ 1300 Super

High-performance diesel engine lubricant proven in new and older high-speed engines



Energy lives here™

Product features

Mobil Delvac™ 1300 Super 15W-40 engine oil meets or exceeds requirements of the API CK-4 and provides cutting-edge performance in diesel engines operating in severe conditions. It can offer:

- Excellent performance in modern, high-output engines (including those with exhaust gas recirculation), and older engines operating on low (500ppm) or ultra-low (15ppm) sulphur diesel fuel
- High-temperature stability and low-temperature characteristics
- Good viscosity control

Excellent protection in Caterpillar, Cummins, John Deere, Mitsubishi and Volvo diesel engines.

Superb resistance to wear

Mobil Delvac 1300 Super engine oil helps control oil thickening caused by soot buildup and exposure to higher temperatures. It possesses outstanding resistance to oxidation, corrosion and wear.

Potential benefits

Mobil Delvac 1300 Super diesel engine oil helps increase vessel reliability by providing:*

- 1** Longer oil life
- 2** Reduced oil consumption and operational costs
- 3** Extended drain intervals

Typical properties

Mobil Delvac 1300 Super	SAE Grade 15W-40
Viscosity, ASTM D 445	
cSt @ 40°C	109
cSt @ 100°C	14
Viscosity Index, ASTM D 2270	
	130
Sulphated Ash, wt%, ASTM D 874	
	0.9
Total Base #, mg KOH/g	
ASTM D 2896	8.56
Pour Point, °C, ASTM D 97	
	-33
Density @ 15°C kg/l, ASTM D 4052	
	0.875

*Compared to conventional, mineral products.